

MD-3U26-RMP



MILITARY | SURVEILLANCE | MACHINE VISION | FACTORY AUTOMATION

MD-3U26-RMP

Specifications



CHASSIS

Material

SGCC 1.2mm thick aluminum chassis and cover with standard finish

Weight

65 lbs. with dual processor motherboard + ATX power supply + (2) hard disks + floppy drive + CD-ROM drive

Front Panel Controls

Power ON/OFF
System Reset switch
Alarm mute switch
2 USB ports

System Indicators

Power On/Off LED
Disk Activity LED
Fan Failure/Overheating Warning LED

Dimensions

Height: 5.25" (132 mm)
Width: 17.00" (430 mm)
Depth: 26.00" (660mm)

COOLING FANS

2 x 60mm rear mounted cooling fan kit
4 x 80mm middle mounted cooling fan kit

POWER

Power Supply

650W Redundant rated switching power supply

ACCESSIBILITY

Two slide and lock top cover design allows quick access to internal components.

(6) horizontal 5.25" drive bays
(3) horizontal 3.5" drive bays

ENVIRONMENT

Operating Temperature

0° to 50° C

Non-Operating Temperature

-20° to 65° C

Humidity

5% to 95% @ 40° C (non-condensing)

Altitude

10,000 feet (3048 m)

Vibration

Non-operating: 5G, 2-200Hz
Operating: 5G, 2-200Hz

Shock

Non-operating: 35G @ 15-20ms
Operating: 2.5G 15-20ms

WARRANTY

ONE YEAR PARTS AND LABOR

Please contact us for ordering and pricing information.

MicroDISC
IMAGE PROCESSING SPECIALISTS

301 Oxford Valley Road, Suite 1502
Yardley, PA 19067

Tel 215.321.9100
Fax 215.321.9190

www.microdisc.com
sales@microdisc.com